



Specifications Ledvance LED  
Downlight Comfort High Efficiency D  
Aluminium White 36W 5200lm 55D -  
840 Cool White | 265mm - Cutout  
250mm - Dali Dimmable

[View Product](#)

## General Information

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| SKU                      | 260330                                                              |
| EAN                      | 4099854687181                                                       |
| manufacturer_code        | 4099854687181                                                       |
| Brand                    | Ledvance                                                            |
| Manufacturer Name        | DOWNLIGHT COMFORT HIGH EFFICIENCY DALI UGR<19 D250 P 36W 840 U19 WT |
| Any Lamp all-in warranty | 5 Years                                                             |
| Average Lifetime (h)     | 100000                                                              |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x26               |
| Wattage                     | 36W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |

|                       |                                |
|-----------------------|--------------------------------|
| Colour of Light       | White                          |
| Light Colour Options  | Single Color                   |
| Beam Angle (degree)   | 55                             |
| Luminous Flux (Lumen) | 5200lm                         |
| Lumen per watt        | 144                            |
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | Opal                           |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 250               |
| IP-Rating              | IP20              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 124 |
| Diameter (mm) | 265 |

## Sensor Information

## Why Any-lamp?

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

 Order from the **largest lighting specialist** in Europe
  **Customised** quotation

 Up to **7 years warranty**
 **Easy** return process